



Product Service

CERTIFICATE

No. U6 17 05 86105 005

Holder of Certificate: AS LED Lighting GmbH

Seeshaupter Str. 2
82377 Penzberg
GERMANY

Certification Mark:



Product:

Luminaires with limited surface temperatures

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. The certification mark must not be altered in any way. See also notes overleaf.

Test report no.:

028-713092609-100



Date, 2017-05-17

(Christian Seidl)

Page 1 of 2

CERTIFICATE

No. U6 17 05 86105 005



Product Service

Model(s):

HCL-050037-xxx-TX-14; HCL-050037-xxx-TX-18;
 HCL-050037-xxx-14- TX-DALI; HCL-050037-xxx-
 TX-18-DALI;
 HCL-057057-xxx- TX-24; HCL-057057-xxx- TX-27;
 HCL-057057-xxx- TX-33; HCL-057057-xxx- TX-24-DALI;
 HCL-057057-xxx- TX-27-DALI; HCL-057057-xxx-
 TX-33-DALI;
 HPL-057057-xxx- TX-24; HPL-057057-xxx- TX-27;
 HPL-057057-xxx- TX-33; HPL-057057-xxx- TX-24-DALI;
 HPL-057057-xxx- TX-27-DALI; HPL-057057-xxx-
 TX-33-DALI
 xxx=Luminaires colour:
 740: CRI=75, 4000K, 840: CRI=85, 4000K,
 850: CRI=85, 5000K, 757: CRI=75, 5700K,
 765: CRI=75, 6500K, 865: CRI=85, 6500K

Parameters:

Rated voltage: 220 - 240 V~
 Rated frequency: 0/50/60 Hz

Rated power:

HCL-050037-xxx-TX-14/HCL-050037-xxx-TX-14-DALI: 119W/700mA
 HCL-050037-xxx-TX-18/HCL-050037-xxx-TX-18-DALI: 152W/700mA
 HCL-057057-xxx-TX-24/HCL-057057-xxx-TX-24-DALI:
 202,5W/700mA
 HCL-057057-xxx-TX-27/HCL-057057-xxx-TX-27-DALI: 228W/700mA
 HCL-057057-xxx-TX-33/HCL-057057-xxx-TX-33-DALI: 277W/700mA
 HPL-057057-xxx-TX-24/HPL-057057-xxx-TX-24-DALI: 204W/700mA
 HPL-057057-xxx-TX-27/HPL-057057-xxx-TX-27-DALI: 227W/700mA
 HPL-057057-xxx-TX-33/HPL-057057-xxx-TX-33-DALI: 277W/700mA

Protection class: I
 Degree of protection: IP64
 Ambient temperature: ta -30°C - +55°C

Tested according to:

EN 60598-1:2015
 EN 60598-2-1:1989
 EN 60598-2-24:2013
 EN 62471:2008

Production Facility(ies):

97410

Page 2 of 2